



COUNTY OF DUPLIN
BUILDING INSPECTIONS DEPARTMENT
 PO BOX 950
 KENANSVILLE, NC 28349
 PHONE: (910) 296-2124 FAX: (910) 296-2166

AFFIDAVIT FOR RESIDENTIAL SWIMMING POOLS, SPAS AND HOT TUBS

I, _____ Owner's name (please print)

Project Address: _____

I will need a safety barrier installed in accordance with the NC State Residential Building Code and all inspection approvals, including final inspection, will be obtained. The NC State Residential Building Code requires private pools to be enclosed by a barrier meeting the requirements of Appendix G. Residential Swimming Pools, Spas and Hot Tubs with permit applications filed after January 1, 2008 must meet at least one of the pool safety barrier requirements (please see options listed below).

Indicate your method of compliance by checking the appropriate answer(s).

___ The pool will be equipped with a powered safety cover in compliance with ASTM F1346.

___ The pool will be equipped with an approved safety pool cover complying with ASTM F- 1346.

___ The pool will be isolated from access from the dwelling and yard by an enclosure meeting the barrier requirements of Residential Code.

___ Combination of a partial barrier, wall of a dwelling serving as a partial barrier, alarms and/or self closing/latching devices:

___ All doors and windows providing direct access from the home to the home to the pool shall be equipped with an exit alarm complying with UL 2017 that has a minimum sound pressure rating of 85 dB A at 10 feet. The exit alarm shall produce a continuous audible warning when the door and its screen are opened. The alarm shall sound immediately after the door is opened and be capable of being heard throughout the dwelling during normal household activities. The alarm shall be equipped with a manual means to temporarily deactivate the alarm for a single opening. Such deactivation shall last no more than 15 seconds. The deactivation switch shall be located at least 54 inches above the threshold of the door. Separate alarms are not required for each door or window if sensors wired to a central alarm sound when contact is broken at any opening.

___ All doors providing direct access from the dwelling to the pool must be equipped with a self-closing, self-latching device with mechanical latching/locking installed a minimum of 54 inches above the threshold, which is acceptable to the authority having jurisdiction so long as the degree of protection afforded is not less than the afforded protection described above.

___The pool or spa shall be designed to produce circulation throughout the area. Suction outlets shall be provided with a cover that conforms with ANSI/ASME A1 12.19.8M, or a 12" by 12" drain grate or larger, or an approved channel drain system (exception of surface skimmers). All outlet circulation systems shall be equipped with atmospheric vacuum relief. The pump circulation systems shall be provided with a minimum of (2) two suction outlets. A minimum of (3) three feet horizontal or vertical distance shall separate such outlets. These suction outlets shall be piped so that water is drawn through them simultaneously through a vacuum relief protected line to the pump or pumps. Inspection access to the interior of the dwelling is required if alarms on windows & doors or if self closing / self latching doors are utilized to meet the above requirement.

Signature (owner)

Witness (signature)

Date

Date

Signature (contractor)

Date

North Carolina
Duplin County

I, _____ I a Notary Public for said county and state, certify that
 _____ appeared before me this day and acknowledge the due
 execution of the foregoing instrument.

Witness my hand and notary seal, this _____ day of _____

Notary Public

My Commission Expires: _____